

# Go! Interior

Economy emulsion paint  
for interior walls and ceilings



THINNING  
0-10%



COVERAGE  
10-12m<sup>2</sup>/L



TOOLS  
brush  
or roller



DRY TO TOUCH  
1-2 hours



Economical emulsion paint for interior walls and ceilings. It is suitable for frequent wall repainting. It covers effectively the wall imperfections, providing a uniform matt finish. It is easy to apply, it spreads evenly.

- » **Very Good Opacity**
- » **Covers effectively wall imperfections**
- » **Suitable for frequent repainting**

## TECHNICAL DATA

<b>Specific Gravity*</b> {ISO 2811 @ 25°C}	1.50-1.64Kg/L
<b>Solids Content w/w*</b> {ISO 3251-03}	65% (±3)
<b>Stormer Viscosity*</b> {ASTM D 562-05 @ 25°C}	110KU (±15)
<b>Application Viscosity*</b> {ASTM D 562-05 @ 25°C}	85KU (±15)
<b>Gloss 60**</b> {ISO 2813-99}	<3.0 units
<b>Gloss 85**</b> {ISO 2813-99}	<13.0 units
<b>pH</b>	8.5-9.5
<b>Whiteness Index**</b> {ASTM E 313-98}	89.0 (±1.5)
<b>Yellowness Index**</b> {ASTM E 313-98}	1.0 (±0.5)
<b>Coverage per coat***</b>	10-12m <sup>2</sup> /L
<b>Recommended Dry Film Thickness</b> (2 coats)	70µm (±5)

\* Depending on the tinting base and the shade.

\*\* Only for White.

\*\*\* Depending on the shade the application conditions and surface absorption.



**Interior matt walls and ceilings A/a (W/B).**

- VOC Limit Value: 30g/L
- Maximum content of VOC of the product in a ready to use condition: 29g/L

# Go! Interior

## Economy emulsion paint for interior walls and ceilings



### SURFACE PREPARATION AND APPLICATION

To ensure good adhesion, the surface must be dry, clean and free of dust, grease, residues, blistered paint etc. Wet sanding is recommended for surface preparation.

- » **On new surfaces:** Before applying the topcoat, apply one coat of a water-based primer such as KRAFT ECO DUR AQUA or KRAFT DUR AQUA WHITE or KRAFT HAFT or KRAFT GO! PLASTERBOARD PRIMER.
- » **On surfaces that need repairing:** use KRAFT SPACHTEL or KRAFT PUTTY or the suitable repairing material of KRAFT.

### APPLICATION INSTRUCTIONS

- » Before you start painting, dilute the paint by up to 10% by volume with tap water and stir well.
- » Appropriate application tools for this product are brush and roller.
- » The product shall be tinted with KRAFT INSPIRED COLOR tinting system to thousands shades. To ensure product quality it is required to tint the corresponding base selected from the tinting system of KRAFT.
- » For shade and finish consistency, it is advisable to use containers of the same batch number. In case of different batch number it is recommended that they be mixed in a large container.
- » Tonal deviation may occur in some shades.
- » Go! INTERIOR White can be mixed with KRAFT MASTER BASICS for plenty of light shades.
- » Apply two coats of KRAFT GO! INTERIOR for the best result.
- » **Minimum recoat time:** 3-4 hours.
- » **Surface drying time:** 1-2 hours at 25°C and 50% relative humidity (drying times are longer in wet/cold conditions).
- » Avoid patching after finishing the painting. The difference of the substrate absorbance and application method might cause colour or gloss deviations. If it is necessary to repair apply the paint to the whole surface.
- » Do not apply at temperatures below 5°C and above 35°C and above 65% relative humidity.

### AFTER USE INSTRUCTIONS

- » Clean the tools thoroughly with water and soap.
- » Close the bucket to maintain in good condition for future use. Store before and after use in a cool place and away from sunlight or frost conditions.

### PACKAGING

- » Available in White in 0.750L, 3L, 9L and Base P in containers of 1L, 3L and 9L.

### HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Read label before use. For further information please refer to the Material Safety Data Sheet.

Poison Centre Telephone:

**+30 210 7793777**

### STORAGE

- » Store the product at temperatures between 5°C to 35°C.

**DISCLAIMER:** The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website [www.kraftpaints.gr](http://www.kraftpaints.gr), as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.

### DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300 ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501  
[www.druckfarben.gr](http://www.druckfarben.gr) | [www.kraftpaints.gr](http://www.kraftpaints.gr)



Toll-free number

**800 111 7700** Monday - Friday, 8.00 am - 04.00 pm

Email: [paints.orders@druckfarben.gr](mailto:paints.orders@druckfarben.gr)