



# FULLY DIP CUT A GLOVES

## FEATURES

- Full hand double nitrile dipping to repel and don't absorb water or oils. First coating layer with smooth nitrile on full hand and second layer with Micro-thin foam on palm and thumb.
- Excellent grip performance with foam nitrile finish on the palm. Nitrile material performs better than others in wide range of temperatures and oily surfaces.
- Nitrile reinforcement coating on thumb to provide durability on a weak area.
- Designed to provide all-day comfort, ideal for manufacturing, plumbing, forestry, automotive and transportation, facility management.
- SMARTSWIPE™ fingertips - allows the use of touch screen devices without removing gloves.
- European Certified for cut protection and heat protection: EN ISO 21420, EN388:2016 (4221A), EN 407 (X1XXX).

## TECHNICAL INFORMATION

**CUT LEVEL (COLOUR CODE):**

CUT LEVEL A (WHITE)

**COLOR OF THE GLOVE:**

RED

**MATERIAL:**

POLYESTER. COATING: NITRILE.

**GAUGE:**

15

**SIZE RANGE:**

FULLY DIP CUT A GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

## UNIT GUIDE

SIZE	ARTICLE NUMBER	PACK QUANTITY	ARTICLE NUMBER	PACK QUANTITY
7 / S	4932493218	1	4932493223	12
8 / M	4932493219	1	4932493224	12
9 / L	4932493220	1	4932493225	12
10 / XL	4932493221	1	4932493226	12
11 / XXL	4932493222	1	4932493227	12



**STAY SAFE.  
STAY PRODUCTIVE.**







Disclaimer  
Information present within  
this sheet was correct at  
the date of issue.

Techtronic Industries GmbH  
71364 Winnenden  
Germany  
milwaukeetool.eu



# FULLY DIP CUT A GLOVES

## CARE INSTRUCTIONS

- |  |   |
|--|---|
|  WASHING, NORMAL PROCESS, MAXIMUM WASHING TEMPERATURE 40° CELSIUS |  NO CHEMICAL CLEANING    |
|  DO NOT IRON   |  DO NOT BLEACH          |
|  NO TUMBLER   |  MAX. 5 WASHING CYCLES |

## STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C -35°C. Storage humidity: 20%-75%

## USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity of rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold objects, very sharp objects which impact the hands with great force or speed. If tear level  $\geq 1$  then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

## USAGE INSTRUCTIONS

Gloves can be used out of the pack 5 years after production date, printed on the glove. Glove life time in use is based on wear and abrasion.



Disclaimer  
Information present within  
this sheet was correct at  
the date of issue.

Techtronic Industries GmbH  
71364 Winnenden  
Germany  
milwaukeetool.eu