

Part of the ROCKWOOL Group

Rockfon[®] Industrial[™] Black

Datasheet



Sounds Beautiful

Rockfon[®] Industrial[™] Black

- Black finish which can be used in their own right to create a ceiling or be placed behind other surfaces
- Low weight (4.0kg/m²), quick and easy to install
- Highest sound absorption (Class A)

Product Description

- Stone wool tile
- Visible side: pre-finished surface
- Rear side: back fleece

Application Areas

- Industry
- Education

Edge	Module size	Weight	MS / MS easy access	Recommended
detail	(mm)	(kg/m²)	(mm)	installation System
A24	1200 x 600 x 50	4.0	50 / 200	Rockfon® System T24 A™

MS = Minimum Suspension



Performance



Sound absorption α_w : up to 1.00 (Class A)

$\alpha_{ m p}$	1.0 0.9 0.8 0.7 0.6 0.5 0.4 0.3 0.2 0.1 0.0 125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	α _w	Absorption class	NRC	
50 / 200	0.55	0.90	1.00	1.00	1.00	1.00	1.00	А	1.00	
50 / 50	0.20	0.70	1.00	1.00	1.00	1.00	1.00	A	1.00	



Reaction to fire

A1



Humidity and sag resistance Up to 100% RH.

No visible deflection in high humidity C/ON



Hygiene

Cleaning - Vacuum

Stone wool provides no sustenance to microorganisms



Environment

Fully recyclable stone wool The recycled content of Rockfon products is between 29% and 64% according to ISO 14021. Rockfon acoustic solutions are Cradle to Cradle Certified® Silver and Bronze (depending on product type).



161

Carbon footprint

3.48 kg of CO2 eq. (cradle to gate based on EPD)

Indoor environment

A selection of Rockfon products have been awarded the Finnish M1 emission classification for building materials and the Danish Indoor Climate Label for low emission products



Thermal insulation Thermal conductivity:

 $\lambda_D = 37 \text{ mW/mK}$



Rockfon[®] is a registered trademark of the ROCKWOOL Group.

- in linkedin.com/company/Rockfon-as
- 🦻 pinterest.com/Rockfon
- youtube.com/RockfonOfficial
- facebook.com/RockfonOfficial
- instagram.com/Rockfon_Official

Sounds Beautiful



ROCKWOOL Limited T/A Rockfon 14th Floor, Chiswick Tower, 389 Chiswick High Road, London W4 4AL Tel: +44 (0) 208 222 7457 www.rockfon.co.uk

Rockfon